

Hiab XS 211 Basic data

Technical data	EP-5 Duo	EP-5 HiDuo	E-6 HiDuo
Max. lifting capacity (kNm)	172	183	180
Outreach, hydraulic extensions (m)	15.1	15.1	16.6
Outreach / lifting capacity (m / kg)	2.7 / 6500	2.7 / 6900	2.5 / 7100
	4.7 / 3750	4.7 / 3950	4.5 / 4050
	6.5 / 2520	6.5 / 2700	6.1 / 2800
	8.4 / 1840	8.4 / 1980	8.0 / 1980
	10.5 / 1400	10.5 / 1500	9.9 / 1500
	12.7 / 1120	12.7 / 1200	12.0 / 1180
	15.0 / 940	15.0 / 1020	14.2 / 960
	-	-	16.5 / 820
Slewing angle (°)	190 - 410	190 - 410	190 - 410
Height in folded position (mm)	2385	2385	2385
Width in folded position (mm)	2500	2500	2500
Installation space needed (mm)	1162	1162	1192
Weight, "standard" crane without stabilizers (kg)	2690	2700	2840
Weight, stabilizer equipment (kg)	334 - 422	334 - 422	334 - 422

Technical data	EP-4 HiPro	EP-5 HiPro	EH-6 HiPro	E-6 HiPro*	E-8 HiPro
Max. lifting capacity (kNm)	193	189	177	173	158
Outreach, hydraulic extensions (m)	12.7	15.1	16.2	24.7	21.0
Outreach / lifting capacity (m / kg)	2.5 / 7400	2.7 / 7100	2.4 / 7500	2.4 / 7500	2.6 / 6700
	4.6 / 4300	4.7 / 4100	4.5 / 4000	4.5 / 4000	4.7 / 3600
	6.4 / 2960	6.5 / 2800	6.1 / 2680	6.1 / 2680	6.3 / 2380
	8.3 / 2200	8.4 / 2060	7.9 / 1880	7.9 / 1880	8.1 / 1600
	10.4 / 1700	10.5 / 1580	9.8 / 1380	9.8 / 1380	10.0 / 1100
	12.6 / 1400	12.7 / 1260	11.8 / 1060	11.8 / 1060	12.0 / 800
	-	15.0 / 1060	13.9 / 860	13.9 / 860	14.1 / 580
	-	-	16.1 / 720	16.1 / 720	16.3 / 450
	-	-	-	-	18.6 / 370
	-	-	-	-	20.9 / 320
	Outreach / lifting capacity, with jib (m / kg)	-	-	19.1 / 140	19.1 / 140
-		-	20.8 / 110	20.8 / 110	-
-		-	22.7 / 90	22.7 / 90	-
-		-	24.6 / 80	24.6 / 80	-
Slewing angle (°)	190 - 410	190 - 410	190 - 410	410	410
Height in folded position (mm)	2385	2385	2385	2666	2385
Width in folded position (mm)	2500	2500	2500	2500	2500
Installation space needed (mm)	1162	1162	1240	1240	1247
Weight, "standard" crane without stabilizers (kg)	2630	2760	3230	3380**	3520
Weight, stabilizer equipment (kg)	334 - 422	334 - 422	334 - 422	334 - 422	334 - 422
Weight, jib (kg)	-	-	-	450	-

* All XS 211 ordered with a jib are equipped with an extra sturdy outer boom system.

** Jib 45X-3 excluded.