



	P 15000 L		P 15000 L/3SI		P 15000 L/4SI	
massimo sfilo idraulico / max. hydraulic outreach / max. alcance hidraulico / rallonge hydraulique max. / max. hydraulische Reichweite	8.00 m		9.92 m		11.86 m	
minimo sfilo idraulico / min. hydraulic outreach / min. alcance hidraulico / rallonge hydraulique min. / min. hydraulische Reichweite	4.14 m		4.22 m		4.26 m	
altezza massima / max height above installation level / altura max. desde el filo infer. de la base hauteur de levage au dessus du plan de pose / hubhöhe ab Fahrzeugrahmen	10.20 m		12.10 m		14.00 m	
portate gru base / outreach - lifting capacity / alcances hidraulicos - capacidad / extension - charge hydraulische Reichweite - Hubkraft	4.14 m 6.04 m 8.00 m	3540 kg 2320 kg 1710 kg	4.22 m 6.12 m 8.02 m 9.92 m	3230 kg 2090 kg 1520 kg 1190 kg	4.26 m 6.16 m 8.06 m 9.96 m 11.86 m	3080 kg 1960 kg 1400 kg 1080 kg 880 kg
portata prolunga manuale / outreach with manual extens. - lifting capacity / alcances con prolongas manuales - capacidad / extension avec rallonges manuelles - charge Reichweite mit manuellen Verlängerungen - Hubkraft	10.05 m 12.10 m	1190 kg 880 kg	11.97 m 14.02 m	870 kg 670 kg	13.91 m	670 kg
portata pompa consigliata / recommended pump delivery / caudal bomba aconsejada debit d'huile recommandé / Förderleistung der Hydraulikpumpe	35 l/min		35 l/min		35 l/min	
pressione di lavoro / working pressure / presión de trabajo / pression de travail / Betriebsdruck	298 bar		298 bar		298 bar	
capacità serbatoio / tank capacity / contenance du reservoir / capacidad deposito de aceite Inhalt des Öltanks	80 l		80 l		80 l	
angolo di rotazione / slewing angle / angulo de giro / angle de rotation / Schwenkbereich	402°		402°		402°	
coppia di rotazione / slewing torque / momento de giro / couple de rotation / Drehmoment	17.4 kNm		17.4 kNm		17.4 kNm	
altezza a riposo / height in folded position / hauteur en position repliée / altura en posición de reposo / Höhe ab Fahrzeugrahmen zusammengelegt	2200 mm		2200 mm		2200 mm	
larghezza a riposo / width in folded position / largeur en position repliée / anchura en posición de reposo / Breite zusammengelegt	2400 mm		2400 mm		2400 mm	
peso gru completa di stabilizzatori estensibili e martinetti piedi / crane weight including side extensions and rams of stabilizers / peso de la grua incluidos las extensiones y los cilindros de los estabilizadores / poids grue complète de bequilles extensibles et verins stabilisateurs / Eigengewicht, einschl.-manuell seitlich ausziehbarer Abstützungen	1690 kg		1815 kg		1895 kg	

- - - - - AREA DI LAVORO / WORKING AREA  
 ——— POR TATA CON LIMITATORE DI MOMENTO / LIFT WITH LOAD LIMIT VALVE  
 ——— POR TATA PROLUNGHE MANUALI / MANUAL EXTENSIONS LIFT



Barcelona 938498388  
 Valencia 961344538

Madrid 918951758  
 Vitoria 945365601

[www.transgruas.com](http://www.transgruas.com)  
[info@transgruas.com](mailto:info@transgruas.com)