



## 92.2 / 92.2 V

Type Type Type Tipo	Ausführung Version Exécutation Modelo	Gewicht Weight Poids Peso	Kurz Short Courte Corta	Lang Long Longue Largo	Verlängert Extended Avec rallonge Alargado
	Code	t	t/m	t/m	t/m
92.2 - 5,5/1	A 1	1,17	2,53/3,7	1,72/5,4	1,32/ 7,1
92.2 - 7,3/2	A 2	1,28	2,39/3,8	1,24/7,2	0,95/ 9,0
92.2 - 9,2/3	A 3	1,36	2,28/3,9	0,91/9,1	0,72/10,7
92.2 V - 6,3/1	A 11	1,20	2,20/4,5	1,60/6,2	1,20/ 7,8

### **TEREX | ATLAS 92.2 / 92.2 V**

- Hubmoment, *loadmoment, moment de course, capacidad* 92 kNm
- Schwenkbereich, *slewing angle, g. de basculement, giro* 410°
- Ölmenge, *oilflow, débit d' huile, caudal de aceite* 35 l/min
- Betriebsdruck, *working pressure, pression de marche, presion de trabajo* 280 bar
- Transportposition  
*Travel position*  
*Position transport route*  
*Posicion durante transport* quer zur Fahrtrichtung  
*crosswise*  
*repliable transversalement*  
*plegada transversal*