



		tm lbs.ft	tm lbs.ft	m ft	m ft	°	kNm lbs.ft	Mpa psi	Mpa psi	l/min gal/min	l gal	kg lbs	mm ft	mm ft	mm ft
F215A.22	F235AXP.22	18,9 136704	20,3 146830	8,30 27'2"	4,00 13'1"	400	33,5 24715	31,0 4500	33,0 4790	45-65 12-17	120 32	2265 4993	2530 8'3"	985 3'2"	2410 7'10"
F215A.23	F235AXP.23	18,4 133087	19,8 143213	10,50 34'5"	6,10 20'0"	400	33,5 24715	31,0 4500	33,0 4790	45-65 12-17	120 32	2425 5346	2530 8'3"	985 3'2"	2410 7'10"
F215AC.23	F235ACXP.23	18,7 135257	20,1 145383	9,10 29'10"	5,45 17'10"	400	33,5 24715	31,0 4500	33,0 4790	45-65 12-17	120 32	2330 5136	2530 8'3"	985 3'2"	2410 7'10"
F215A.24	F235AXP.24	17,8 128747	19,2 138874	12,70 41'8"	8,25 27'0"	400	33,5 24715	31,0 4500	33,0 4790	45-65 12-17	120 32	2580 5687	2530 8'3"	985 3'2"	2410 7'10"
F215AC.24	F235ACXP.24	18,3 132364	19,6 141767	11,30 37'0"	7,60 24'11"	400	33,5 24715	31,0 4500	33,0 4790	45-65 12-17	120 32	2490 5489	2530 8'3"	985 3'2"	2410 7'10"
F215A.25	F235AXP.25	17,5 126578	19,0 137427	14,90 48'10"	10,35 33'11"	400	33,5 24715	31,0 4500	33,0 4790	45-65 12-17	120 32	2760 6084	2530 8'3"	985 3'2"	2410 7'10"
F215AC.25	F235ACXP.25	18,0 130194	19,5 141044	13,50 44'3"	9,70 31'9"	400	33,5 24715	31,0 4500	33,0 4790	45-65 12-17	120 32	2630 5789	2530 8'3"	985 3'2"	2410 7'10"
F215A.26	F235AXP.26	16,7 120791	18,6 134534	17,10 56'1"	12,45 40'10"	400	33,5 24715	31,0 4500	33,0 4790	45-65 12-17	120 32	2865 6316	2530 8'3"	985 3'2"	2410 7'10"
F215AC.26	F235ACXP.26	17,3 125131	19,1 138155	15,70 51'6"	11,80 38'8"	400	33,5 24715	31,0 4500	33,0 4790	45-65 12-17	120 32	2770 6106	2530 8'3"	985 3'2"	2410 7'10"



COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV
ISO 9000